

Overview

Rubber Tech™ Bonding Primer is a premium-grade primer specifically engineered for superior adhesion to a wide range of roofing substrates. Designed to prepare surfaces for seamless overcoat application, Rubber Tech™ Bonding Primer ensures long-lasting durability and enhanced performance of your roofing system. Whether for commercial or residential use, Rubber Tech™ Bonding Primer provides the ultimate foundation for a watertight and weather-resistant finish.

Features

-  **Exceptional Adhesion:** ensures superior bonding strength, even on challenging surfaces, creating a stable foundation for long-lasting roof coatings.
-  **Fast Drying:** Reduces wait time, allowing for quicker project turnaround.
-  **UV and Weather Resistant:** Performs effectively under extreme environmental conditions.
-  **Easy Application:** Compatible with brush, roller, or spray techniques.
-  **Enhanced Overcoat Performance:** Improves the longevity and effectiveness of topcoat systems.
-  **Eco-Friendly Formula:** Low VOC and solvent-free, making it safer for applicators and the environment.

Key Features – What makes out product unique:

- Binds Up Un-Sound Surfaces
- Tinted Slightly Red to for applicator to see where it has been used
- Excellent adhesion to Water based coatings
- Improves film hardness
- Abrasion & weather resistance and ability to be cleaned

RubberTech™ Bonding Primer is ideal for:

- Preparing roofs for elastomeric, silicone, or acrylic coatings.
- Sealing uneven or porous surfaces to improve uniformity of overcoats.
- Enhancing adhesion on aged or weathered substrates.
- See technical data sheet s for application instructions.

Packaging Options

10Lt branded drum
20Lt branded drum



For more information, technical support, or custom solutions, contact RWF at 078 735 8466 or visit www.roofwallfloor.co.za



Application Details

- Mixing**
 - Always stir well before use with a flat paddle.
- Application method**
 - Brush, Roller and Airless Spray a coat of Rubber TechLRP High Performance Bonding Primer.
- Thinning**
 - This Product is ready for use un-thinned; thinning with water will reduce its properties/durability.
- Cleaning**
 - Application equipment clean up is with clean tap water.
- Application**
 - Stir well before use.
 - With brush or roller apply a generous coat of the area that needs protecting.
 - Allow to dry 3-4 hours before recoating.
 - With a Brush or roller apply a second generous coat.
 - 2 Coats of Rubber Tech LRP High Performance Bonding Primer are used for best results.
 - This Product is ready for use un-thinned; thinning with water will reduce its Properties/Durability it is also tinted slightly red to see where it has been used
 - Clean tools immediately after use with clean tap water.
 - Do not apply before 09:00 and after 16:00 in the winter.

Surface Preparation

- Previously Painted**
 - Make sure old paint coatings are firm and solid.
- Surfaces**
 - Remove all loose, flaking and bubbling paint.
 - Remove all dust, grease, foreign material, fungal and algae growth.
 - Allow to dry.
 - If then powdery or friable Apply two coats of Rubber Tech LRP High Performance Bonding Primer.

Product Data	Resin Base	Acrylic resin emulsion
	Drying Time	Touch dry: $\pm$ 1 hour Hard dry: $\pm$ 4-6 hours
	Film Thickness	30-40 microns per coat
	Spreading Rate	6-8mSQM per 1litre Although the spreading rate will vary with porosity and type of substrate, for uncoated new surfaces work on 4-6 square meters per litre for the first coat and 8-10 square meters per litre for subsequent coats and for when applied to sealed, previously painted substrates.
Precautions	This Product is not flammable, contains no toxic substances and only low levels of VOC (EU regulations).	

DISCLAIMER

RubberTech™ cannot be held liable if the product fails due to improper surface preparation or application.