

Overview

ClearPrep is a high-performance, elastomeric acrylic resin emulsion specifically designed to protect, seal, and waterproof roofing structures. With its advanced formulation, this liquid rubber sealant creates a seamless, flexible, and durable membrane that adheres to primed surfaces, extending the life of your roof while resisting the harshest environmental elements.

Features

- Prepares the Roof for Other Water Proofing Coatings
- Impedes dirt collection
- Excellent adhesion to Water based coatings
- Improved film hardness
- Abrasion/weather resistance and ability to be cleaned
- Flexible Application
- Expands and contracts with the surface, preventing cracks and splits caused by thermal movement.
- Eco-Friendly & Non-Toxic

Free of VOCs, solvents, and harmful chemicals, making it safe for installers and the environment.

Easy Application

Ready-to-use formula suitable for brush, roller, or spray application.

Superior Adhesion

Adheres securely to various roofing substrates, including metal types such as galvanized steel, aluminum, and tin.

Application

- Professional application on primed roofing structures (residential, commercial, and industrial buildings)
- Flashings, gutters, valleys, and downspouts
- Securing roof fasteners such as screws, bolt and rivets
- HVAC systems and rooftop equipment bases
- Storage tanks, containers, and metal structures
- Used as first layer in liquid rubber

Packaging Options

- 10Lt branded drum
- 20Lt branded drum



For more information, technical support, or custom solutions, contact RWF at 078 735 8466 or visit www.roofwallfloor.co.za



TECHNICAL DATA & INFORMATION

Application

- Stir well before use.
- With brush or roller apply a generous coat of the area that needs protecting.
- Allow to dry 3-4 hours before recoating.
- With a Brush or roller apply a second generous coat.
- 2 Coats of Rubber Tech LRP™ Clear prep are used for best results.
- This Product is ready for use un-thinned; thinning with water will reduce its properties/durability
- Clean tools immediately after use with clean tap water.
- Do not apply before 09:00 and after 16:00 in the winter.

Surface Preparation

- Previously Painted Surfaces**
- Make sure old paint coatings are firm and solid.
 - Remove all loose, flaking and bubbling paint.
 - Remove all dust, grease, foreign material, fungal and algae growth.
 - Allow to dry.
 - If then powdery or friable, seal with Rubber Tech LRP™ Clear prep.
 - Apply two coats of Rubber Tech LRP™ Clear prep.

Product Data	Resin Base	Acrylic resin emulsion
	Drying Time	Touch dry: $\pm$ 1 hour Hard dry: $\pm$ 4-6 hours
	Film Thickness	30-40 microns per coat
	Spreading Rate	6-8mSQM per 1litre Although the spreading rate will vary with porosity and type of substrate, for uncoated new surfaces work on 4-6 square meters per litre for the first coat and 8-10 square meters per litre for subsequent coats and for when applied to sealed, previously painted substrates.x
Precautions	This Product is not flammable, contains no toxic substances and only low levels of VOC (EU regulations).	

DISCLAIMER

RubberTech™ cannot be held liable if the product fails due to improper surface preparation or application.