

Overview

Liquid Rubber Paint with Rust Prevention is a next-generation, water-based acrylic elastomeric coating designed to provide superior waterproofing and corrosion protection in one product. This superior corrosion-inhibiting formula ensures excellent adhesion to metal surfaces while forming a seamless, flexible, and durable waterproofing membrane. Engineered for long-lasting protection, it prevents water penetration, and shields metal surfaces from rust and degradation.

Our advanced formulation of Liquid Rubber Paint™ with added RostGuard™ (LRP with RostGuard) is a game-changer in metal surface protection. Specifically formulated for metal roofs with a built-in rust inhibitor and mold inhibitor. This unique coating creates a flexible, waterproof barrier and further prevents corrosion and microbial growth, even the harshest environments. It's the ultimate solution for dependable protection. Backed by a 10-year product and workmanship warranty, it's the smart, long-lasting solution for metal roof maintenance and restoration.

Features

-  **Waterproof Barrier:** Creates a watertight seal to prevent water penetration into the substrate. Applied in several layers and strengthened with a suitable woven material it forms a thick protective membrane for roof sealing.
-  **Flexible & Durable:** Creates a watertight seal to prevent water penetration into the substrate. Applied in several layers and strengthened with a suitable woven material it forms a thick protective membrane for roof sealing.
-  **UV Resistant:** Creates a watertight seal to prevent water penetration into the substrate. Applied in several layers and strengthened with a suitable woven material it forms a thick protective membrane for roof sealing.
-  **Eco-Friendly:** Free of solvents, VOCs, and harmful chemicals, making it safe for use indoors and outdoors.
-  **Versatile Application:** Can be successfully applied on galvanized sheeting, roofing felt, tiles, slate, and shingles. Can also be used on window ledges and to seal parapet wall tops.
-  **Seamless Finish:** Provides a smooth, uniform coating that enhances the surface's appearance performance.
-  **Easy Application:** Can be applied using a brush, roller, or airless sprayer.
-  **Rust & Corrosion Prevention:** Protects and prevents metal surfaces from oxidation and rust development.

Key Features

- Water ingress prevention with rust prevention and mold inhibitor in one product
- Available in a range of popular roof shades as well as white.
- Based on a highly flexible and highly water/Weather resistant Acrylic resin emulsion
- Remains highly flexible for years even after extended exposure to the environment.
- Excellent adhesion. Quick drying two coats can be applied in one day.
- Low odor.

Application

- Stir well before use.
- With brush or roller, Or Spray apply a generous/thick coat of to the area that needs protecting in small manageable sections.
- Firmly and evenly press a layer of woven fabric waterproofing membrane such as Biddimin to the wet layer of LRP with RostGuard™
- Allow to dry 4-6 hours before recoating.
- Apply a second, third and possibly a fourth generous coat, waiting 4-6 hours between coats, until the membrane is totally saturated and the surface has an even and very noticeable high sheen.
- This Product is ready for use un-thinned; thinning with water will reduce its hiding power and effectiveness.
- Three to four coats of this product are used for best results.
- Application equipment clean up is with clean tap water.
- Do not apply before 09:00 and after 16:00 in the winter.
- Do not apply exterior if it looks like rain will occur within 4-6 hours of application

Surface Preparation

- | | |
|--|---|
| Rusted Metal | <ul style="list-style-type: none"> • Affected areas need to be cleaned back to bright metal and spot primed with LRP with RostGuard™ . • Remove collected sand and dust from the area. • Apply 3-4 coats of LRP with RostGuard™ |
| New Metal | <ul style="list-style-type: none"> • Degrease surfaces with a Galvanized Iron Cleaner to remove the manufacturer's grease protective layer. This process is repeated until the surface is water break free. • Rinse well with potable water. • Paint the Clean Degreased Meta Apply 3-4 coats of LRP with RostGuard™ |
| Uncoated cement Plaster surfaces | <ul style="list-style-type: none"> • Remove dust, foreign material, fungal and algae growth. • Fill all visible cracks and seal with Rubber Roof Plaster Primer™. • Apply 3-4 coats of LRP with RostGuard™ |
| Fibre Cement Surfaces (Uncoated Weathered or New) | <ul style="list-style-type: none"> • Remove dust, foreign material, fungal and algae growth. • If friable or powdery, seal with RubberTech Bonding Primer™ • Apply 3-4 coats of LRP with RostGuard™ |
| Previously Painted | <ul style="list-style-type: none"> • Make sure old paint coatings are firm and solid. • Remove all loose, flaking and bubbling paint. • Remove all dust, grease, foreign material, fungal and algae growth. • Allow to dry. • If then powdery or friable, seal with RubberTech Bonding Primer™. • Apply 3-4 coats of LRP with RostGuard™. |

Ideal for use on:

- Interior and exterior
- Rust Free metal and wooden substrates
- Seal nail heads and roofing bolts.
- Roofs (metal, concrete, asphalt, tile, wood, and more)
- Gutters and downspouts
- Metal structures and exposed steel
- Industrial, commercial, and residential waterproofing projects

Product Data	Resin Base	Acrylic resin emulsion
	Drying Time	Touch dry: $\pm$ 1 hour Hard dry: $\pm$ 4-6 hours much Longer in Cold Damp Weather
	Film Thickness	Circa 100-150 microns per coat
	Spreading Rate	1-3 SQM per 1 liter Although the spreading rate will vary with porosity and type of substrate, for uncoated new surfaces work on 0.5-1 square meters per liter for the first coat and 2-3 square meters per liter for subsequent coats and for when applied to sealed, previously painted substrates.
Application Details	Mixing	Always stir well before use with a flat paddle.
	Application Method	Airless Spray Brush and Roller
	Thinning	This Product is ready for use un-thinned; thinning with water will reduce its hiding power.
	Cleaning	Application equipment clean-up is with clean tap water.
Precautions	This Product is not flammable, contains no toxic substances and only low levels of VOC (EU regulations).	

DISCLAIMER

RubberTech™ cannot be held liable if the product fails due to improper surface preparation or application.

Packaging Options

- 10Lt branded drum
- 20Lt branded drum

For more information,
technical support or custom solutions
contact RWF at 078 735 8466
visit www.roofwallfloor.co.za



Colour Options

